



## KANGA 5, 6 & 7 B SERIES OPERATORS MANUAL



[WWW.KANGALoader.COM](http://WWW.KANGALoader.COM)

1300 4 KANGA

# SPECIFICATIONS - 6 SERIES

PERFORMANCE	GB622		DB625	
Max. Lift Capacity	250 kg	551 lbs	250 kg	551 lbs
Travel Speed	7 km/h	4.3 mph	7.5 km/h	4.7
Operating Weight (Machine Only with water filled tyres)	866 kg	1909 lbs	975 kg	2150 lbs
Fuel Capacity	54 L	12.94 US gal	54 L	14.2 hp
<b>ENGINE</b>				
Manufacturer	Honda GX690		Kubota D902	
Power	16.5 KW	22.1 hp	17.5 KW	23.4 hp
<b>DRIVE SYSTEM</b>				
Drive Control	Soft Touch Hand Levers		Soft Touch Hand Levers	
Throttle Control	Hand Levers		Hand Lever	
Wheels	Direct Drive Hydraulics Motors		Direct Drive Hydraulic Motors	
<b>HYDRAULICS</b>				
Gear Pump Displacement	11.3 cc/rev	0.69 cu.in/rev	12.5 cc/rev	0.76 cu.in/rev
Pump Output	41 L/min	10.75 US gal/ min	45 L/min	11.9 US gal/min
System Pressure	207 bar	3000psi	220 bar	3200 psi
Hyd. Reservoir Capacity	66 L	17.4 US gal	66 L	17.4 US gal
<b>BUCKETS</b>				
Standard Bucket Capacity	0.1 m <sup>3</sup>	3.5 cu.ft	0.1m <sup>3</sup>	3.5 cu.ft
4 in 1 Bucket Capacity	0.1 m <sup>3</sup>	3.5 cu.ft	0.1m <sup>3</sup>	3.5 cu.ft
<b>DIMENSIONS</b>				
<b>A</b> Max Operating Height	2500mm	98.4"	2500mm	98.4"
<b>B</b> Height to Hinge Pin	1855mm	73"	1855mm	73"
<b>C</b> Overall Height	1340mm	52.8"	1340mm	52.8"
<b>D</b> Overall Length With Bucket	2200mm	86.6"	2200mm	86.6"
<b>E</b> Overall Wheel Width	1030mm	40.6"	1030mm	40.6"
<b>F</b> Bucket Reach at 40°	410mm	16.1"	410mm	16.1"
Bucket Max Reach (Level)	1020mm	40.1"	1020mm	40.1"
<b>G</b> Dump Height Std. Bucket	1130mm	44.5"	1130mm	44.5"
Dump Height 4 in 1 Bucket	1855mm	43.3"	1855mm	43.3"
<b>H</b> Bucket Width	1050mm	41.3"	1050mm	41.3"
<b>I</b> Bucket Max Roll Back	40°		40°	
<b>J</b> Bucket Max Dump Angle	60°		60°	
<b>K</b> Ground Penetration	430mm	16.9"	430mm	16.9"
<b>L</b> Overall Length Less Bucket	1660mm	65.4"	1660mm	65.4"
<b>M</b> Ground Clearance	185mm	7.3"	185mm	7.3"
<b>N</b> Angle of Departure	40°		40°	
Approach Angle	90°		90°	

# DIMENSIONS - 6 SERIES

